

-60/-30°C
-45/-10°C

Low Temperature ChestFreezers

REMEMBER YOUR QUOTE ON OPTIONALS

LTF series

As a synonym for security, the LTF series gives reliable low temperature freezing, with good temperature uniformity. Digital display, alarms, contact for remote monitoring, basket(s) and castors are some of the standards.

LTFE series

Engineered for just a little bit more, the LTFE series gives you -45°C instead of the conventional -40°C. Equipped with digital display and alarm features these freezers give the security needed for safe sample storage at low temperatures.

LTF / LTFE series

- Single compressor
- Low energy consumption
- Low noise level
- 100% HCFC/CFC free
- Key lock, castors and baskets

Controller features

- Digital display
- Visual and acoustic alarm
- Adjustable high/low temperature alarm
- Contact for remote alarm
- Probe failure alarm

ACCESSORIES AVAILABLE



Racks and boxes (optional).



Prepared for our advanced CO2 backup system (optional).



5 racks and 40 pieces 50mm plastic boxes. (optional for LTF 85)



21 racks and 216 pieces 50mm plastic boxes. (optional for LTF 325 / LTFE 290)



27 racks and 282 pieces 50mm plastic boxes. (optional for LTF 535 / LTFE 515)



Ihr Fachhändler:
MS-L GmbH
Kälte- und Temperiertechnik

Schönbornstr. 7
D-69234 Dielheim bei Heidelberg

Tel: (0)6222 / 93 56-60
Fax: (0)6222 / 93 56-66
eMail: info@MS-L.de

Model	LTF 85	LTF 325	LTF 425	LTF 535
Item code (DAI no.)	DAI101	DAI111	DAI116	DAI121
Dimensions exterior WxDxH (mm)	552x648x850	1262x698x885	1562x698x885	1662x758x925
Net capacity (L)	71	284	368	476
Temperature range (°C)	-30/-60	-30/-60	-30/-60	-30/-60
Power supply (V)	230	230	230	230
Frequency (Hz)	50/60	50/60	50/60	50/60

Model	LTFE 140	LTFE 290	LTFE 370	LTFE 515
Item code (DAI no.)	DAI 1600	DAI1605	DAI1610	DAI1615
Dimensions exterior WxDxH (mm)	722x698x885	1055x655x865	1305x655x865	1662x758x890
Net capacity (L)	130	284	368	476
Temperature range (°C)	-10/-45	-10/-45	-10/-45	-10/-45
Power supply (V)	230	230	230	230
Frequency (Hz)	50/60	50	50	50

We reserve the right to change specifications without notice. Subject to confirmation and availability.